



RRT-25IDE

2.5" IDE/ATA/PATA Solid State Drive (SSD)

- Drop in replacement for obsolete 2.5" IDE/ATA/PATA drives
- ATA/ATAPI-7
- Transfer rates up to 150 MB/s
- Capacities up to 480 GB
- Commercial temperature range (0°C to 70°C)
- Extended temperature range (-40°C to 85°C)
- Conformal coating available
- RoHS compliant
- US-based engineering and manufacturing
- In-house technical support



2.5" IDE/ATA/PATA SOLID STATE DRIVE (SSD) offers a long-term industrial grade solution for replacement of obsolete 2.5" IDE/ATA drives from Seagate, Western Digital, Hitachi and IBM.

Our unique product is designed for 2.5" form factor and does not use SATA/PATA adapters.

ORDERING INFORMATION

RRT-25IDE- SLC - 8GB - UR - X

Requirements

NAND Flash Type

SLC	Single Level Cell
MLC	Multi Level Cell

Capacity

0GB - 60GB	SLC
60GB - 240GB	MLC

Options May be left blank

<u>Extended Temperature Range</u>	
X	-40°C to 85°C

Conformal Coating

UR	Polyurethane
AR	Acrylic

ORDER EXAMPLES

RRT-25IDE-SLC-60GB-UR-X-R
RRT-25IDE-MLC-120GB

Product Specifications

2.5" IDE/ATA/PATA SOLID STATE DRIVE (SSD)

PERFORMANCE

NAND FLASH TYPE	SLC	MLC
CAPACITIES ¹	Up to 60GB	Up to 240GB
INTERFACE	Standard 2.5" ATA/IDE 44-pin connector	
THROUGHPUT	Up to 150 MB/S	
SECTOR SIZE	512 byte	

RELIABILITY

MTBF (HOURS) ²	650,000 hours	
DATA RETENTION	10 years ³	1 year ⁴
ENDURANCE (100GB SSD)	350 TBW	70 TBW

POWER

VOLTAGE	+5V +/- 5%	
WATTS (IDLE)	0.5 W	
WATTS (ACTIVE)	2 W max	

ENVIRONMENTAL

OPERATING TEMP.	0 °C to 70 °C	
EXTENDED OPERATING TEMP.	-40 °C to 85 °C	
STORAGE TEMP.	-45 °C to 90 °C	
RELATIVE HUMIDITY	5% to 95% non-condensing	
ALTITUDE	80,000 ft. (24,000 meters)	
SHOCK	50g 11 millisecond	
VIBRATION	12.0g 20 Hz to 2000 Hz	

PHYSICAL

FORM FACTOR	2.5" drive	
WEIGHT	3.5 oz (99.2 g)	
DIMENSIONS	2.8" x 3.9" x 0.5" (70.0mm x 100.00mm x 12.5mm)	

NOTES

- (1) Larger capacities available as new media is released
- (2) Telcordia SR-332, Issue 3, operating temp. (40 °C), electrical stress (50%), environmental factor (1.0)
- (3) SLC: 10 years at 10% TBW ramping down to 1 year at 100% TBW
- (4) MLC: 10 years at 0% TBW ramping down to 1 year at 100% TBW



Red Rock Technologies, Inc. reserves the right to modify, change or discontinue specific products within its product line at its own discretion. Red Rock Technologies, Inc. does not assume any liability resulting from the application or use of its products. The information contained herein has been checked and is believed to be entirely accurate; however, no responsibility is assumed for inaccuracies. "Red Rock Technologies" and the mountain logo are registered trademarks of Red Rock Technologies, Inc.

© Copyright 2023 Red Rock Technologies, Inc.
All rights reserved. (Rev. 20230426a)