


## RRT-GUVME-SATA-DVD 6U VME SATA DVD Module

- SATA interfaces via VME P0 and/or P2 connector
- Provides removable boot disk and/or storage
- Compatible with off-the-shelf DVD/CD utility software
- P2 SATA adapter accessory available
- ROHS compliant



THE 6U VME SATA DVD MODULE uses low-profile COTS DVD drive. Modes of operation include DVD-ROM, DVD-R/W, CD-ROM and CD-R/W. SATA 2 compliant interface.

## **Ordering Information**

ATA Drive Module	
	RRT-6UVME-SATA-DVD-P2- UR
Options May be left blank	
Conformal Coating	
UR Polyurethane AR Acrylic	
	ORDER EXAMPLES
	RRT-6UVME-SATA-DVD-P0 RRT-6UVME-SATA-DVD-P2-UR

(480)-483-3777

## **Product Specifications**

## **6U VME SATA DVD MODULE**

PERFORMANCE	
CAPACITIES	CD/DVD capacities
INTERFACE <sup>1</sup>	SATA2
	RELIABILITY
MTBF - DRIVE MODULE <sup>2</sup>	60,000 hours
	POWER
VOLTAGE	+5V +/- 5%
WATTS (IDLE)	2.5 W
WATTS (ACTIVE)	5 W
	ENVIRONMENTAL
OPERATING TEMP.	5°C to 45°C
STORAGE TEMP.	-20°C to 65°C
RELATIVE HUMIDITY (OPERATING)	8% to 80%
RELATIVE HUMIDITY (NON-OPERATING)	5% to 95%
ALTITUDE	10,000 ft. (3,000 meters)
SHOCK (OPERATING)	5G, 11mS; half sine
SHOCK (NON-OPERATING)	20G, 11mS; half sine
VIBRATION (OPERATING)	0.3G horizontal mounted, 0.2G vertically mounted, 5Hz to 500Hz, sine sweep rate of 1.0 oct/min
VIBRATION (NON-OPERATING)	2G (zero to peak), 5Hz to 500Hz to 10Hz and sweep rate of 1.0 oct/min
	PHYSICAL
FORM FACTOR	6U VME
WEIGHT	24 oz. max (681 g)
PITCH	1.0"
	PHYSICAL
(1) Interface connected via P0 or P2. (2) Telcordia SR-322, issue 3, operating temp (4)	OC), electrical stress (50%), environmental factor (1.0)

(2) Telcordia SR-322, issue 3, operating temp (40C), electrical stress (50%), environmental factor (1.0)



Red Rock Technologies, Inc. reserves the right to modify, change or discontinue specific products within its product line at its own discretion. Red Rock Technologies, Inc. does not assume any liability resulting from the application or use of its products. The information contained herein has been checked and is believed to be entirely accurate; however, no responsibility is assumed for inaccuracies. "Red Rock Technologies" and the mountain logo are registered trademarks of Red Rock Technologies, Inc. © Copyright 2023 Red Rock Technologies, Inc. All rights reserved. (Rev. 20230112a)

(480)-483-3777 •