





RRT-XMC-CFast-R-A XMC Removable CFast Module: Air Cooled

XMC REMOVABLE CFAST MODULE: AIR COOLED is a mezzanine storage module with a PCI Express SATA 3 controller that supports one Removable CFast.

Provides boot drive and/or disk storage for VPX, VME, cPCI and ATCA single board computers (SBCs) with XMC Slot. CFast is same form factor as Compact Flash but with SATA interface, thus providing faster throughput. The CFast connectors are rated for 10,000 mating cycles to support frequent insertions/removals.

- XMC PCIe Gen 2x1 interface per VITA 42.3
- Transfer rates up to 500 MB/s
- CFast capacities up to 1TB
- CFast connectors rated for 10,000 mating cycles
- Air cooled
- Wide range of COTS CFast options
- CFast secured by rugged retainer clip
- High performance SATA3 transfer rates. Backwards compatible with SATA1/2
- Compatible with all SBCs with XMC slot
- Meets XMC VITA 42 height requirements
- -X version rated for -40°C to 85°C
- CFast with write protect switch available
- Front panel activity LED
- VxWorks, Linux, and Windows driver support
- ROHS compliant



Ordering Information

XMC Removable CFast Module: Air Cooled

RRT-XMC-CFast-R-A- **UEFI64** - **UR** - **X**

Requirements

BIOS

UEFI64	UEFI BIOS for 64-bit system
UEFI32	UEFI BIOS for 32-bit system
Legacy	Legacy BIOS for older systems

Options May be left blank

<u>Extended Temperature Range</u>	
X	-40°C to 85°C

Conformal Coating

UR	Polyurethane
AR	Acrylic

ORDER EXAMPLES

RRT-XMC-CFast-R-A-UEFI64
RRT-XMC-CFast-R-A-Legacy-UR-X

CFast Card

RRT-CFAST- **SLC** - **8GB** - **X** - **WP**

Requirements

NAND Flash Type

SLC	Single Level Cell
MLC	Multi Level Cell
TLC	Tri Level Cell (3D)

Capacity

4GB - 64GB	SLC
8GB - 512GB	MLC
32GB - 1TB	TLC

Options May be left blank

Write Protect

WP	Write Protect
----	---------------

Extended Temperature Range

X	-40°C to 85°C
---	---------------

ORDER EXAMPLES

RRT-CFAST-MLC-512GB
RRT-CFAST-SLC-8GB-X-WP



Product Specifications

XMC REMOVABLE CFAST MODULE: AIR COOLED

PERFORMANCE

CAPACITIES	Up to 1TB
XMC INTERFACE	VITA 42.3/PCIe 2.0x1 Compliant
XMC INTERFACE SPEED (PCIe GEN1/GEN2)	2.5/5Gbits/s
CFAST INTERFACE	SATA 3 backwards compatible with SATA 1/2
SECTOR SIZE	512 bytes

RELIABILITY

MTBF - XMC MODULE ¹	3 million hours
--------------------------------	-----------------

POWER

VOLTAGE	VPWR +5V +/- 5% or +12V +/- 5%, +3.3+/- 0.3V
WATTS (IDLE)	1.2 W
WATTS (ACTIVE)	2.5 W

ENVIRONMENTAL

OPERATING TEMP., VITA 47 CLASS	0 °C to 70 °C, AC1
EXTENDED OPERATING TEMP., VITA 47 CLASS ²	-40°C to 85°C, AC3
STORAGE TEMP.	-55 °C to 95 °C
ALTITUDE	80,000 ft. (24,000 meters)
RELATIVE HUMIDITY	5% to 95% non-condensing
SHOCK, VITA 47 CLASS ³	40g, 11 millisecond terminal sawtooth pulse
VIBRATION ⁴	0.1g ² /Hz

PHYSICAL

FORM FACTOR	XMC
WEIGHT	3.5 oz. (100g max)

NOTES

- (1) Telcordia SR-322, Issue 3, operating temp (40C), electrical stress (50%), environmental factor (1.0).
- (2) Thermal qualification per MIL-STD-810, Method 501 Procedure II, and MIL-STD-810, Method 502, Procedure II.
- (3) Shock qualification per MIL-STD-810F, Method 516, Procedure I.
- (4) Vibration qualification per MIL-STD-810F, Method 514, Procedure I.



Red Rock Technologies, Inc. reserves the right to modify, change or discontinue specific products within its product line at its own discretion. Red Rock Technologies, Inc. does not assume any liability resulting from the application or use of its products. The information contained herein has been checked and is believed to be entirely accurate; however, no responsibility is assumed for inaccuracies. "Red Rock Technologies" and the mountain logo are registered trademarks of Red Rock Technologies, Inc.

© Copyright 2023 Red Rock Technologies, Inc.
All rights reserved. (Rev. 20230426a)