



Applications

- High-Speed Communications
- Optical Communications

Summary

The **FMC-RCP-4G** is an FMC I/O module with up to four 4Gb/s Optical transceiver channels.

Based on the FMC Standard (VITA 57.1) but with modified profile and increased front IO area to accommodate the optical transceivers.

Suitable for use in harsh environments with LuxCis optical connectors and full speed operation over the industrial temperature range.

Deliverables

FMC-RCP-4G Board
One Year Warranty
One Year Technical Support

Board Features

- 1 or 2 ARINC 801 Connectors

Input/Output Interfaces

1x 4 Optical Links - 850nm (4 Tx & 4 Rx)



Support

FMC Pinout available in User Manual

Environmental Specification
Temperature Ranges

Cooling Option	Operating Temperatures		Storage Temperatures	
	Min	Max	Min	Max
AC1	-40°C	70°C	-55°C	100°C
CC1	-40°C	70°C	-55°C	100°C

Operating Humidity : Up to 95% (non-condensing)

EMC Standards

 FCC 47CFR Part 2
 EN55022:2010 Equipment ClassB

Conformal Coating Options

 Acrylic or Polyurethane
 Contact sales for specification of coatings.

Ordering Information
Order Code: FMC-RCP-4G/I(f0)(c)(a)

Option	Code	Description of Options
Lanes	I	2 = 2 Tx + 2 Rx Lanes (one RCP Module), 4 = 4 Tx + 4 Rx Lanes (two RCP Module)
Reference Frequency	f0	blank = 156.250MHz, /xxx.yyy (specify frequency in MHz)
Cooling	c	blank = air cooled industrial, /CC1 = conduction cooled industrial
Conformal Coating	a	blank = none, A = Acrylic, P = Polyurethane

 Address: 160 Dundee Street, Suite 4A,
 Edinburgh, EH11 1DQ, UK
 Telephone: +44 131 558 2600
 Fax: +44 131 558 2700
 email: sales@alpha-data.com
 website: http://www.alpha-data.com

 Address: 611 Corporate Circle Suite H
 Golden, CO 80401
 Telephone: (303) 954 8768
 Fax: (866) 820 9956 - toll free
 email: sales@alpha-data.com
 website: http://www.alpha-data.com