

MP3X21

TRIPLE DISPLAY PORTABLE COMPUTER



PORTABLE COMPUTING SYSTEM

Our MP3X21 portable computer systems are ready for jobs where a laptop isn't enough, but you can't bring your desktop where you need to go. Offering extensive screen space, excellent processing and a variety of plug-in options, these systems are a good fit for your portable computing requirements.

APPLICATIONS

- Telemetry
- Diagnostics
- Simulation
- C4ISR
- Communications
- Imaging
- Persistent Surveillance
- IJA\/s
- Automation

FEATURES

- 3x 21.5" FHD 1920x1080 Monitors
- Rugged Aluminum Alloy Construction
- Detachable Keyboard with Touch Pad
- (6x) 3-1/2" and (3x) 5-1/4" drive bays
- Preconfigured for Turnkey Operation
- Long-life Components
- Expansive Screen Space
- Ready for Transport
- Excellent Processing Power
- Built-in 3W Speaker

Who We Are

CP Technologies designs, fabricates and integrates standard and customized high-performance computing platforms and LCD monitors for military, industry, and commercial applications.

Using COTS components, CP Technologies provides solutions for customers who need reliable systems that will operate in a variety of harsh conditions and who require revision control and hardware consistency for multi-year programs.

CP Technologies is an ITAR Registered and ISO 9001:2015 Certified business that has been operating in Southern California for over twenty years.

Assembled in the USA ISO 9001:2015 Certified ITAR Registered

CP Technologies 2620 Deep Well Ranch Rd Prescott, AZ 86301 combatproven.tech 858.571.4330



TECH SPECS

DIMENSIONS 15.3" X 21.1" X 11.7" (388.6mm X 535.9mm X 297.2mm)

Deployed: 15.3" X 59.1" X 11.7" (388.6mm X 1501.1mm X 297.2mm)

WEIGHT 65lbs; weight varies by configuration

CONSTRUCTION Heavy duty, cold-rolled electroplated steel

Rubber corner bumpers

FRONT USB PORTS (2x) ports USB 2.0

COOLING FANS (2x) 120mm cooling fan

MOTHERBOARD CAPACITY Designed for ATX-sized motherboard (9.6" X 12"), (7x) I/O cards slots

POWER 750W 100/240 Volt AC, PS2 Form Factor, Other power options available

COMPUTER SPECS

CPU Intel Core and Xeon Processors supported

MOTHERBOARD Varies by configuration, ATX Form Factor

MEMORY Varies by configuration

STORAGE (6x) 3.5" and (3x) 5.25"

OPTICAL DRIVE Slimline DVD-RW

EXPANSION SLOTS (x7) Full Height I/O Cards

RAID Varies by configuration

ENVIRONMENTAL SPECS

TEMPERATURE -20°C~60°C Non-Operating, 0°C~50°C Operating

HUMIDITY 10%~95%

CERTIFICATIONS CE, FCC, RoHS

ENGINEERED TO YOUR SPECIFICATIONS

- In-house engineering department
- Design and build of rapid prototypes. Experience with solving difficult customer application problems through knowledge of the industry and custom system design and manufacturing capability
- Our Engineers use Solid Works 3D CAD modeling software for mechanical design and thermal simulation
- Design experience with MIL-STD-167, MIL-STD-461, MIL-STD-810, and MIL-S-901, in addition to FCC, UL, CE, and country specific agency requirements

REVISION CONTROL & CONFIGURATION MANAGEMENT

- Our Program Managers will assure your products are revision controlled for the life of the program
- Configuration Management to assure TAA Compliance and system compatibility
- One part number for life of the program
- · Counterfeit and obsolescence management

FACILITY AND TEST

PANEL SPECS

SCREEN DIAGONAL

CONTRAST RATIO

VIEWING ANGLE

RESPONSE TIME

BRIGHTNESS

BACKLIGHT

COLORS

NATIVE RESOLUTION

- All integration work is performed in a state-of-the-art, ESD-controlled facility
- Our facility has 23,000 sqft and has dedicated 12,000 sqft to manufacturing and 3,000 sqft to engineering

QUALITY COUNTS

- ISO 9001:2015 Certified
- 100% system inspection before shipment
- All integrated systems undergo a minimum 24-hour system test and burn-in before shipment to the customer
- Assistance with 3rd party verification of system
- 5-year warranty on all servers and 3-year warranty on LCD monitor products
- TAA compliant
- · Built in the USA

CP Technologies 2620 Deep Well Ranch Rd

Prescott, AZ 86301

21.5"

5ms

LED

16.7M

1000:1

80° (L/R/U/D)

1920x1080

250 cd/m2