



# RAR15X

## High Density MIL-STD-1553 and ARINC 429 XMC Embeddable Module

Abaco Systems' embeddable RAR15X is the latest generation of performance and flexibility for MIL-STD-1553A/B Notice II and ARINC 429 on a XMC.0 Mezzanine Card. The RAR15X includes advanced API (Application Programming Interface) software that reduces application development time.

### MIL-STD-1553 Features

Standard features include 64-bit, 25 nanosecond receive message time tagging, extensive BC & RT link-list structures, error injection/detection, automatic/manual RT Status Bit and Mode Code responses, along with advanced BC functionality.

With the multi-function configuration, all channels operate independently and are easily configured to operate with a simultaneous Bus Controller, up to 31 Remote Terminals and Bus Monitor functionality. With the Dual-function configuration, the RAR15X interfaces have all the features of the multi-function version, supporting either Bus Monitor and Bus Controller or Bus monitor and 31 Remote terminals.

The RAR15X Bus Monitor provides unparalleled error detection and 100% monitoring of fully loaded buses.

Conductive cooling and conformal coating is standard on the RAR15X.

### ARINC 429 Features

Standard features include independent 64-bit, 1 microsecond receive message time tagging as well as common 64-bit, 25 nanosecond receive message time tagging, large transmit and receive message buffers, and a message scheduler providing total flexibility in generating ARINC bus traffic scenarios.

Transmit features include independent software programmable data rates and parity generation with message length and gap error injection. Simultaneous Scheduled and Burst Mode (FIFO) messaging is supported on all ARINC 429 transmit channels.

Receive features include independent, software programmable data rates, parity reporting, and message error detection. Each ARINC 429 receive channel provides simultaneous Dedicated and Buffered Mode storage, along with label/SDI filtering.

### Software

Abaco provides our advanced 1553 and ARINC 429 API's in source code along with support for Microsoft® Windows®, Linux®, and VxWorks®. Contact your local sales person for additional operating system support.

### FEATURES:

- 2 or 4 dual-redundant MIL-STD-1553A/B Notice II channels
- 10 ARINC 429 Receive channels
- 4 or 8 ARINC 429 Transmit channels
- Bi-directional Avionics level discretes individually configurable as 1553 output or input triggers.
- XMC.3 (PCIe) host interface
- Simultaneous Bus Controller, up to 31 Remote Terminals and Bus Monitor
- Multi-function or Dual-function (BC and BM or RT and BM) 1553 operation
- High-level API for Microsoft® Windows®, Linux®, and VxWorks® included. Contact your local sales person for additional operating system support.
- MIL-STD-1760 level compatible
- Flexible Hardware Remote Terminal Addressing
- Complete message programmability
- Error injection/detection
- Flexible message status/interrupt generation

### Timing

- IRIG receiver
- External differential time-tag reset and clock inputs
- 64-bit, 25 nanosecond message time-tagging

### Environmental

- Standard conductively cooled, conformal coated
- RoHS compliant to EU directive 2002-95-EC
- P16 or P14 Rear I/O

# RAR15X High Density MIL-STD-1553 and ARINC 429 XMC Embeddable Module

## Specifications

### Physical

- XMC Mezzanine Card (74mm x 143.75 mm without bezel)
- Rear I/O interface

### Environmental

- Standard conduction cooled rear I/O operating temperature range: -40°C to +85°C (at the XMC rail)
- Relative humidity: Up to 95% (non-condensing)

### Software Support

- API – High-level libraries with source code included for Microsoft Windows, Linux, and VxWorks. Contact your local sales person for supported software.

### ARINC 429 Receive Channels

- 10 receive channels
- Data rates: 12.5 KHz, 100 KHz or 5 KHz to 150 KHz programmable
- Standard input levels: ±6.5 to ±13 VDC (A to B)
- Filtering: Label and/or SDI
- Parity: Odd/Even detection

### ARINC 429 Transmit Channels

- 8 Transmit channels
- Data rates: 12.5 KHz, 100 KHz or 5 KHz to 150 KHz programmable
- Transmit Output level: ±10 VDC (A to B)
- Parity: Odd, even or none
- Transmit error injection option: message gap, high or low bit count

### Power (4 channels at 75% duty cycle into transformer coupled bus)

- VPWR (+5 or +12)
- Quiescent = 240 mA @12V
- Power 25% channel transmit rate = 500mA@12V
- Power 75% channel transmit rate = 900mA@12V

### On-board Shared RAM

- 8 Mbyte

### Timing

- Independent 64-bit, 25ns message time-tagging per channel
- Time can be programmed via the host or by a 1553 trigger
- All timers can be synchronized to 0 via the host
- Timers can independently use IRIG time
- IRIG-B single ended
- Selectable External time-tag clock input provided
- Selectable External time tag reset input provided

## Descriptions

### Multi-function Operational Modes

- Simultaneous BC, 31 RTs and BM

### Dual-function Operational Modes

- BC and BM or 31 RTs and BM

### Bus Controller

- Programmable control over major and minor frame content and timing – Inter-message gap times
- Programmable control over response time-out and late response
- Modify messages, data or setup on the fly
- Insert aperiodic messages into a running BC list
- Conditional message sequencing based on real-time message data or status
- Selectable interrupt generation and status messages on full range of system conditions or all detected errors
- Programmable error injection (on a per word basis) See Full error detection/injection table below
- Synchronize BC operation to external time source or trigger
- Multiple BC data buffers

### Full error detection/injection

- Invalid word
- Bit count error
- High word
- Low word
- Inverted sync
- Manchester
- Late response
- Early response
- No response
- Incorrect RT address
- Parity error
- Invalid command

### Remote Terminal

- Multiple RT simulation (up to 31 RTs)
- Programmable error injection (on a per word basis) See Full error detection/injection table previous
- Modify data, status words or setup while card is running
- Programmable message content
- Selectable interrupts
- RT Map Monitoring

### Bus Monitor

- Capture 100% fully loaded bus traffic with:
  - Time-tagging
  - Error status
  - Word status
  - Message status
- Interrupts can be selected by RT / SA / WC
- Extensive filtering and triggering options
  - By individual RT/subaddress
  - Transmit, receive or broadcast mode codes
  - Internal or external triggering
  - Trigger output on user specified data
- Real-time bus playback with RT edit mode
- IRIG/GPS synchronization

### Optional Configurations

- P14 or P16 rear I/O
- Dual or Multi-function
- Contact factory for custom requirements

## Ordering information

<b>RAR15X-1042DC</b>	MIL-STD-1553 and ARINC 429 XMC Interface card with 10RX, 4TX, ARINC 429 channels; 2 Ch Dual-Function 1553, P16 Rear I/O, -40°C to +85°C Operating temp, Fixed volt, XFMR Coupled, Conformal coated, Conductive cooled, 12 Avionics discretes
<b>RAR15X-1042MC</b>	MIL-STD-1553 and ARINC 429 XMC Interface card with 10RX, 4TX, ARINC 429 channels; 2 Ch Multi-Function 1553, P16 Rear I/O, -40°C to +85°C Operating temp, Fixed volt, XFMR Coupled, Conformal coated, Conductive cooled, 12 Avionics discretes
<b>RAR15X-1044DC</b>	MIL-STD-1553 and ARINC 429 XMC Interface card with 10RX, 4TX, ARINC 429 channels; 4 CH Dual-Function 1553, P16 Rear I/O, -40C TO +85C Operating temp, Fixed volt, XFMR Coupled, Silicon Conformal coated, Conductive cooled, 12 Avionics discretes
<b>RAR15X-1044MC</b>	MIL-STD-1553 and ARINC 429 XMC Interface card with 10RX, 4TX, ARINC 429 channels; 4 CH Multi-Function 1553, P16 REAR I/O, -40C TO +85C Operating temp, Fixed volt, XFMR Coupled, Conformal coated, Conductive cooled, 12 Avionics discretes
<b>RAR15X-1084DC</b>	MIL-STD-1553 and ARINC 429 XMC Interface card with 10RX, 8TX, ARINC 429 channels; 4 Ch Dual-Function 1553, P16 Rear I/O, -40°C to +85°C Operating temp, Fixed volt, XFMR Coupled, Conformal coated, Conductive cooled, 6 Avionics discretes
<b>RAR15X-1084MC</b>	MIL-STD-1553 and ARINC 429 XMC Interface card with 10RX, 8TX, ARINC 429 channels; 4 Ch Multi-Function 1553, P16 Rear I/O, -40°C to +85°C Operating temp, Fixed volt, XFMR Coupled, Conformal coated, Conductive cooled, 6 Avionics discretes

Note: P14 rear I/O configurations available upon request.

WE INNOVATE. WE DELIVER. YOU SUCCEED.

Americas: 866-OK-ABACO or +1-866-652-2226 Asia & Oceania: +81-3-5544-3973

Europe, Africa, & Middle East: +44 (0) 1327-359444

Locate an Abaco Systems Sales Representative visit: [abaco.com/products/sales](http://abaco.com/products/sales)

[abaco.com](http://abaco.com) | [@AbacoSys](https://twitter.com/AbacoSys)

©2019 Abaco Systems. All Rights Reserved. All other brands, names or trademarks are property of their respective owners. Specifications are subject to change without notice.

